



## Mechanical

Dimensions	66 x 202 x 32 mm (2.6 x 7.95 x 1.26")
Weight	Without stand: 223 g (7.86 oz) With stand: 336 g (11.85 oz)
Enclosure material	Polycarbonate
Mount materials	Stand: aluminum Wall mount: polycarbonate

## Hardware

Processor	74 Kc MIPS Processor at 775 MHz
Memory	128 MB DDR2
Management interface	Ethernet
Networking interface	(2) 10/100/1000 MbE RJ45 ports WP7607 LTE
SIM	Nano SIM
LTE bands	CAT4, B1/3/7/8/20/28
LCM display	1.54" screen
Button	Factory-reset
Power method	PoE+, Passive PoE (48V)
Power supply	UniFi PoE switch 48V, 0.5A PoE adapter
Supported voltage range	44–57V DC
Max. power consumption	8.5W
MIMO	U-LTE 2 x 2 Category 4 LTE Radio
Throughput speed*	Download 150 Mbps Upload 50 Mbps <small>*Speed and coverage depend on location and network performance.</small>

Antenna gain	LTE	B1	2 dBi
		B3	1.5 dBi
		B7	2 dBi
		B8	3.5 dBi
		B20	2 dBi
		B28	2 dBi

Mounting	Wall mount or foot stand (included)
ESD/EMP protection	Air/Contact: ± 24 kV
Operating temperature	-10 to 60° C (-14 to 140° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

