

## Talk Telephone Adapter



## Mechanical

Dimensions	131.5 x 110.7 x 28.2 mm (5.18 x 4.36 x 1.11")
Weight	300 g (10.58 oz)
Enclosure material	Plastic

## Display

Display size	86.04 mm (3.39") diagonal
Resolution	192 x 64 dots

## Hardware

Memory	RAM: 128 Mb DDR3 Storage: 256 Mb
Power method	USB-C 5V DC, 1A PoE 48V DC/0.35A
Power supply	5VDC, 1A power adapter, 1.5 m cord (included) PoE (pair B 4, 5+; 7, 8-)
Connectivity	(1) 100 MbE RJ45 port/PoE (1) 3.5 mm (0.14") headset port (2) RJ11 FXS ports (1) USB-C (power input)  802.11a/b/g/n/ac WiFi 2.4G b/g/n, BW 20 WiFi 5G a/n/ac, BW 20/40/80
Buttons	(3) Device control keys
Telephone features	Voicemail, DND, caller ID, call transfer, call waiting, 3-way conference
Operating temperature	0 to 40° C (32 to 104° F)
Operating humidity	10 to 90% noncondensing
Certifications	FCC, IC, CE

## Software

Fax over IP	Fax pass-through using G.711
Voice codec	G.711 u/a
Number of supported phone lines	2
UniFi OS application	UniFi Talk (version 1.12.0 and later)
Minimum software requirements	Web browser (Chrome™ recommended)

