G4 Doorbell





Mechanical

Dimensions	118.3 x 46.8 x 25.8 mm (4.66 x 1.84 x 1.02")
Weight	Without mount: 130 g (4.59 oz) With flat wall mount: 178 g (6.28 oz) With 20° wedge mount: 200 g (7.05 oz)
Enclosure material	Polycarbonate
Mount materials	Flat wall mount: aluminum alloy 20° wedge mount: polycarbonate
Weatherproofing	IPX4

Optics

Sensor	5 MP CMOS sensor
Lens	Fixed focal length
View angle	H: 138°, V: 114°, D: 155°
Night mode	Built-in IR LED illumination and IR cut filter

Video

Video compression	H.264
Resolution	1600 x 1200 (4:3)
Maximum frame rate	30 FPS

System

Quad-core Arm® Cortex®-A53 based chip
802.11 ac WiFi
12VA
16-24V AC, 20VA
Yes
Factory reset
Tactory reset
Flat wall/20° wedge (kits included)
Flat wall/20° wedge (kits included)

Audio

Microphone	Yes (can be disabled in software)
Speaker	Yes



Software

Controller software	UniFi Protect
Mobile apps	UniFi Protect iOS™ and Android™

Compatibility

Compatible chimes

	Manufacturer	Model
Mechanical	Broan-NuTone	LA126WH
	Broan-NuTone	LA11WH
	Heath Zenith	SL-2735
	Craftmade	CTPW-RG
	Broan-NuTone	LA39WH
	Newhouse Hardware	CHM3D
Digital	Broan-NuTone	LA600WH
	IQ AMERICA	DW-2850
	IQ AMERICA	DW-2840

Transformer Specifications

Input rating (5, 6)	230V, 50/60Hz
Output rating (1, 4)	16VA C, 15VA
Operating temperature	-5 to 35 ° C (23 to 95° F)

